

Entrance Mats & anti slip

Architectural Building Products

Doormat

- Type: T2

- Description: Stair nosing for slip-resistant insert, made of aluminium, countersunk drilled

- Application: protection of the stair nosing's corners

- Length of the profile: 1 m , 1.2 m, 1.5 m , 2 m , 3 m , 6 m

- Width of the profile: 50 mm

- Height of the profile: 30 mm

- Alloy of the profile: Aluminium 6063

- Anodized colours: silver, gold,

- Additional colours: aluminium polished

- Fixation: screwing, countersunk drilled holes 3.5 mm

Installation/Laying

1. The metal stair nosings have countersunk holes in their dovetailing guides (into which the inserts are subsequently fitted). They are fastened on the step by screwing them (for stair use dowels). A perfect glue bond was successfully obtained,

2. The PVC-insert should be cut to the desired fixed size in cold condition.

3. The two next expansion joint on the back side allow to compress the tempered insert (at room temperature) and to fix it easily overhand into the dovetailing guide of the metal stair nosing

Attention! Very important! The PVC-insert will normally be taken to the building site in cold condition. Naturally the PVC-insert is so rigid in that condition that it can hardly be compressed. Then it is very important to heat the insert in room temperature. This condition is obtained when the insert can be compressed by your fingers. Take care, however, not to heat the insert more than necessary, because otherwise it will tend first to expand and then to shrink

